

Package: audubon (via r-universe)

August 31, 2024

Title Japanese Text Processing Tools

Version 0.5.2

Description A collection of Japanese text processing tools for filling Japanese iteration marks, Japanese character type conversions, segmentation by phrase, and text normalization which is based on rules for the 'Sudachi' morphological analyzer and the 'NEologd' (Neologism dictionary for 'MeCab'). These features are specific to Japanese and are not implemented in 'ICU' (International Components for Unicode).

License Apache License (>= 2)

URL <https://github.com/paithiov909/audubon>,
<https://paithiov909.github.io/audubon/>

BugReports <https://github.com/paithiov909/audubon/issues>

Depends R (>= 2.10)

Imports dplyr (>= 1.1.0), magrittr, Matrix, memoise, purrr, readr,
rlang (>= 0.4.11), stringi, V8

Suggests roxygen2, spelling, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

Language en-US

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Repository <https://paithiov909.r-universe.dev>

RemoteUrl <https://github.com/paithiov909/audubon>

RemoteRef HEAD

RemoteSha 93f1767d6fc3281b071c152cce6726b248cb2216

Contents

bind_lr	2
bind_tf_idf2	3
collapse_tokens	5
get_dict_features	5
hiroba	6
lex_density	7
mute_tokens	8
ngram_tokenizer	8
pack	9
polano	10
prettify	10
read_rewrite_def	11
strj_fill_iter_mark	12
strj_hiraganize	12
strj_katakanize	13
strj_normalize	14
strj_rewrite_as_def	14
strj_romanize	15
strj_segment	16
strj_tinyseg	17
strj_tokenize	18
strj_transcribe_num	19
Index	20

bind_lr	<i>Bind importance of bigrams</i>
---------	-----------------------------------

Description

Calculates and binds the importance of bigrams and their synergistic average.

Usage

```
bind_lr(tbl, term = "token", lr_mode = c("n", "dn"), avg_rate = 1)
```

Arguments

tbl	A tidy text dataset.
term	<data-masked> Column containing terms as string or symbol.
lr_mode	Method for computing 'FL' and 'FR' values. n is equivalent to 'LN' and 'RN', and dn is equivalent to 'LDN' and 'RDN'.
avg_rate	Weight of the 'LR' value.

Details

The 'LR' value is the synergistic average of bigram importance that based on the words and their positions (left or right side).

Value

A data.frame.

See Also

[doi:10.5715/jnlp.10.27](https://doi.org/10.5715/jnlp.10.27)

Examples

```
prettify(hiroba, col_select = "POS1") |>
  mute_tokens(POS1 != "\u540d\u8a5e") |>
  bind_lr() |>
  head()
```

bind_tf_idf2

Bind term frequency and inverse document frequency

Description

Calculates and binds the term frequency, inverse document frequency, and TF-IDF of the dataset. This function experimentally supports 4 types of term frequencies and 5 types of inverse document frequencies.

Usage

```
bind_tf_idf2(
  tbl,
  term = "token",
  document = "doc_id",
  n = "n",
  tf = c("tf", "tf2", "tf3", "itf"),
  idf = c("idf", "idf2", "idf3", "idf4", "df"),
  norm = FALSE,
  rmecab_compat = TRUE
)
```

Arguments

<code>tbl</code>	A tidy text dataset.
<code>term</code>	<data-masked> Column containing terms.
<code>document</code>	<data-masked> Column containing document IDs.
<code>n</code>	<data-masked> Column containing document-term counts.
<code>tf</code>	Method for computing term frequency.
<code>idf</code>	Method for computing inverse document frequency.
<code>norm</code>	Logical; If passed as TRUE, TF-IDF values are normalized being divided with L2 norms.
<code>rmeCab_compat</code>	Logical; If passed as TRUE, computes values while taking care of compatibility with 'RMeCab'. Note that 'RMeCab' always computes IDF values using term frequency rather than raw term counts, and thus TF-IDF values may be doubly affected by term frequency.

Details

Types of term frequency can be switched with `tf` argument:

- `tf` is term frequency (not raw count of terms).
- `tf2` is logarithmic term frequency of which base is $\exp(1)$.
- `tf3` is binary-weighted term frequency.
- `itf` is inverse term frequency. Use with `idf="df"`.

Types of inverse document frequencies can be switched with `idf` argument:

- `idf` is inverse document frequency of which base is 2, with smoothed. 'smoothed' here means just adding 1 to raw values after logarithmizing.
- `idf2` is global frequency IDF.
- `idf3` is probabilistic IDF of which base is 2.
- `idf4` is global entropy, not IDF in actual.
- `df` is document frequency. Use with `tf="itf"`.

Value

A data.frame.

Examples

```
df <- dplyr::count(hiroba, doc_id, token)
bind_tf_idf2(df) |>
  head()
```

collapse_tokens	<i>Collapse sequences of tokens by condition</i>
-----------------	--

Description

Concatenates sequences of tokens in the tidy text dataset, while grouping them by an expression.

Usage

```
collapse_tokens(tbl, condition, .collapse = "")
```

Arguments

tbl	A tidy text dataset.
condition	<data-masked> A logical expression.
.collapse	String with which tokens are concatenated.

Details

Note that this function drops all columns except but 'token' and columns for grouping sequences. So, the returned data.frame has only 'doc_id', 'sentence_id', 'token_id', and 'token' columns.

Value

A data.frame.

Examples

```
df <- prettify(head(hiroba), col_select = "POS1")
collapse_tokens(df, POS1 == "\u540d\u8a5e")
```

get_dict_features	<i>Get dictionary's features</i>
-------------------	----------------------------------

Description

Returns dictionary's features. Currently supports "unidic17" (2.1.2 src schema), "unidic26" (2.1.2 bin schema), "unidic29" (schema used in 2.2.0, 2.3.0), "cc-cedict", "ko-dic" (mecab-ko-dic), "naist11", "sudachi", and "ipa".

Usage

```
get_dict_features(
  dict = c("ipa", "unidic17", "unidic26", "unidic29", "cc-cedict", "ko-dic", "naist11",
    "sudachi")
)
```

Arguments

dict Character scalar; one of "ipa", "unidic17", "unidic26", "unidic29", "cc-cedict", "ko-dic", "naist11", or "sudachi".

Value

A character vector.

See Also

See also **'CC-CEDICT-MeCab'**, and **'mecab-ko-dic'**.

Examples

```
get_dict_features("ipa")
```

hiroba	<i>Whole tokens of 'Porano no Hiroba' written by Miyazawa Kenji from Aozora Bunko</i>
--------	---

Description

A tidy text data of audubon::polano that tokenized with 'MeCab'.

Usage

```
hiroba
```

Format

An object of class `data.frame` with 26849 rows and 5 columns.

Examples

```
head(hiroba)
```

lex_density	<i>Calculate lexical density</i>
-------------	----------------------------------

Description

The lexical density is the proportion of content words (lexical items) in documents. This function is a simple helper for calculating the lexical density of given datasets.

Usage

```
lex_density(vec, contents_words, targets = NULL, negate = c(FALSE, FALSE))
```

Arguments

vec	A character vector.
contents_words	A character vector containing values to be counted as contents words.
targets	A character vector with which the denominator of lexical density is filtered before computing values.
negate	A logical vector of which length is 2. If passed as TRUE, then respectively negates the predicate functions for counting contents words or targets.

Value

A numeric vector.

Examples

```
head(hiroba) |>
  prettify(col_select = "POS1") |>
  dplyr::group_by(doc_id) |>
  dplyr::summarise(
    noun_ratio = lex_density(POS1,
      "\u540d\u8a5e",
      c("\u52a9\u8a5e", "\u52a9\u52d5\u8a5e"),
      negate = c(FALSE, TRUE)
    ),
    mvr = lex_density(
      POS1,
      c("\u5f62\u5bb9\u8a5e", "\u526f\u8a5e", "\u9023\u4f53\u8a5e"),
      "\u52d5\u8a5e"
    ),
    vnr = lex_density(POS1, "\u52d5\u8a5e", "\u540d\u8a5e")
  )
```

mute_tokens	<i>Mute tokens by condition</i>
-------------	---------------------------------

Description

Replaces tokens in the tidy text dataset with a string scalar only if they are matched to an expression.

Usage

```
mute_tokens(tbl, condition, .as = NA_character_)
```

Arguments

- tbl A tidy text dataset.
- condition <data-masked> A logical expression.
- .as String with which tokens are replaced when they are matched to condition. The default value is NA_character.

Value

A data.frame.

Examples

```
df <- prettify(head(hiroba), col_select = "POS1")
mute_tokens(df, POS1 %in% c("\u52a9\u8a5e", "\u52a9\u52d5\u8a5e"))
```

ngram_tokenizer	<i>Ngrams tokenizer</i>
-----------------	-------------------------

Description

Makes an ngram tokenizer function.

Usage

```
ngram_tokenizer(n = 1L)
```

Arguments

- n Integer.

Value

ngram tokenizer function

pack	<i>Pack a data.frame of tokens</i>
------	------------------------------------

Description

Packs a data.frame of tokens into a new data.frame of corpus, which is compatible with the Text Interchange Formats.

Usage

```
pack(tbl, pull = "token", n = 1L, sep = "-", .collapse = " ")
```

Arguments

tbl	A data.frame of tokens.
pull	<code><data-masked></code> Column to be packed into text or ngrams body. Default value is token.
n	Integer internally passed to ngrams tokenizer function created of <code>audubon::ngram_tokenizer()</code>
sep	Character scalar internally used as the concatenator of ngrams.
.collapse	This argument is passed to <code>stringi::stri_c()</code> .

Value

A tibble.

Text Interchange Formats (TIF)

The Text Interchange Formats (TIF) is a set of standards that allows R text analysis packages to target defined inputs and outputs for corpora, tokens, and document-term matrices.

Valid data.frame of tokens

The data.frame of tokens here is a data.frame object compatible with the TIF.

A TIF valid data.frame of tokens are expected to have one unique key column (named `doc_id`) of each text and several feature columns of each tokens. The feature columns must contain at least token itself.

See Also

<https://github.com/ropenscilabs/tif>

Examples

```
pack(strj_tokenize(polano[1:5], format = "data.frame"))
```

polano	<i>Whole text of 'Porano no Hiroba' written by Miyazawa Kenji from Aozora Bunko</i>
--------	---

Description

Whole text of 'Porano no Hiroba' written by Miyazawa Kenji from Aozora Bunko

Usage

```
polano
```

Format

An object of class character of length 899.

Details

A dataset containing the text of Miyazawa Kenji's novel "Porano no Hiroba" which was published in 1934, the year after Kenji's death. Copyright of this work has expired since more than 70 years have passed after the author's death.

The UTF-8 plain text is sourced from <https://www.aozora.gr.jp/cards/000081/card1935.html> and is cleaned of meta data.

Source

https://www.aozora.gr.jp/cards/000081/files/1935_ruby_19924.zip

Examples

```
head(polano)
```

prettify	<i>Prettify tokenized output</i>
----------	----------------------------------

Description

Turns a single character column into features while separating with delimiter.

Usage

```
prettify(
  tbl,
  col = "feature",
  into = get_dict_features("ipa"),
  col_select = seq_along(into),
  delim = ",",
)
```

Arguments

tbl	A data.frame that has feature column to be prettified.
col	<data-masked> Column name where to be prettified.
into	Character vector that is used as column names of features.
col_select	Character or integer vector that will be kept in prettified features.
delim	Character scalar used to separate fields within a feature.

Value

A data.frame.

Examples

```
prettify(
  data.frame(x = c("x,y", "y,z", "z,x")),
  col = "x",
  into = c("a", "b"),
  col_select = "b"
)
```

read_rewrite_def	<i>Read a rewrite.def file</i>
------------------	--------------------------------

Description

Read a rewrite.def file

Usage

```
read_rewrite_def(
  def_path = system.file("def/rewrite.def", package = "audubon")
)
```

Arguments

def_path	Character scalar; path to the rewriting definition file.
----------	--

Value

A list.

Examples

```
str(read_rewrite_def())
```

strj_fill_iter_mark	<i>Fill Japanese iteration marks</i>
---------------------	--------------------------------------

Description

Fills Japanese iteration marks (Odori-ji) with their previous characters if the element has more than 5 characters.

Usage

```
strj_fill_iter_mark(text)
```

Arguments

text	Character vector.
------	-------------------

Value

A character vector.

Examples

```
strj_fill_iter_mark(c(
  "\u3042\u3044\u3046\u309d\u3003\u304b\u304d",
  "\u91d1\u5b50\u307f\u3059\u309e",
  "\u306e\u305f\u308a\u3033\u3035\u304b\u306a",
  "\u3057\u308d\u2033\u2035\u3068\u3057\u305f"
))
```

strj_hiraganize	<i>Hiraganize Japanese characters</i>
-----------------	---------------------------------------

Description

Converts Japanese katakana to hiragana. It is almost similar to `stringi::stri_trans_general(text, "kana-hira")`, however, this implementation can also handle some additional symbols such as Japanese kana ligature (aka. goryaku-gana).

Usage

```
strj_hiraganize(text)
```

Arguments

text	Character vector.
------	-------------------

Value

A character vector.

Examples

```
strj_hiraganize(
  c(
    paste0(
      "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
      "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
      "\u3068\u304a\u3063\u305f\u98a8"
    ),
    "\u677f\u57a3\u6b7b\u30b9\u0002a708"
  )
)
```

strj_katakanize	<i>Katakanize Japanese characters</i>
-----------------	---------------------------------------

Description

Converts Japanese hiragana to katakana. It is almost similar to `stringi::stri_trans_general(text, "hira-kana")`, however, this implementation can also handle some additional symbols such as Japanese kana ligature (aka. goryaku-gana).

Usage

```
strj_katakanize(text)
```

Arguments

`text` Character vector.

Value

A character vector.

Examples

```
strj_katakanize(
  c(
    paste0(
      "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
      "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
      "\u3068\u304a\u3063\u305f\u98a8"
    ),
    "\u672c\u65e5\u309f\u304b\u304d\u6c37\u89e3\u7981"
  )
)
```

strj_normalize	<i>Convert text following the rules of 'NEologd'</i>
----------------	--

Description

Converts characters into normalized style following the rule that is recommended by the Neologism dictionary for 'MeCab'.

Usage

```
strj_normalize(text)
```

Arguments

text	Character vector to be normalized.
------	------------------------------------

Value

A character vector.

See Also

<https://github.com/neologd/mecab-ipadic-neologd/wiki/Regexp.ja>

Examples

```
strj_normalize(
  paste0(
    "\u2015\u2015\u5357\u30a2\u30eb\u30d7\u30b9",
    "\u306e\u3000\u5929\u7136\u6c34-\u3000\u30ff33",
    "\uff50\u41\u52\u4b\u49\u4e\u47*",
    "\u3000\u2c\u45\u4d\u4f\u4e+",
    "\u3000\u30ec\u30e2\u30f3\u4e00\u7d5e\u308a"
  )
)
```

strj_rewrite_as_def	<i>Rewrite text using rewrite.def</i>
---------------------	---------------------------------------

Description

Rewrites text using a 'rewrite.def' file.

Usage

```
strj_rewrite_as_def(text, as = read_rewrite_def())
```

Arguments

text	Character vector to be normalized.
as	List.

Value

A character vector.

Examples

```
strj_rewrite_as_def(
  paste0(
    "\u2015\u2015\u5357\u30a2\u30eb",
    "\u30d7\u30b9\u306e\u3000\u5929",
    "\u7136\u6c34-\u3000\u3033\u303f",
    "\uff41\uff52\uff4b\uff49\uff4e\uff47*",
    "\u3000\u303c\u303d\u303e\u303f\u3040\u3041",
    "\u3000\u30ec\u30e2\u3033\u3040\u3042\u3043\u3044\u3045\u3046\u3047\u3048\u3049"
  )
)
strj_rewrite_as_def(
  "\u60e1\u3068\u5047\u9762\u306e\u30eb\u30fc\u30eb",
  read_rewrite_def(system.file("def/kyuji.def", package = "audubon"))
)
```

strj_romanize

Romanize Japanese Hiragana and Katakana

Description

Romanize Japanese Hiragana and Katakana

Usage

```
strj_romanize(
  text,
  config = c("wikipedia", "traditional hepburn", "modified hepburn", "kunrei", "nihon")
)
```

Arguments

text	Character vector. If elements are composed of except but hiragana and katakana letters, those letters are dropped from the return value.
config	Configuration used to romanize. Default is wikipedia.

Details

There are several ways to romanize Japanese. Using this implementation, you can convert hiragana and katakana as 5 different styles; the wikipedia style, the traditional hepburn style, the modified hepburn style, the kunrei style, and the nihon style.

Note that all of these styles return a slightly different form of `stringi::stri_trans_general(text, "Any-latn")`.

Value

A character vector.

See Also

<https://github.com/hakatashi/japanese.js#japaneseromanizetext-config>

Examples

```
strj_romanize(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  )
)
```

strj_segment	<i>Segment text into tokens</i>
--------------	---------------------------------

Description

An alias of `strj_tokenize(engine = "budoux")`.

Usage

```
strj_segment(text, format = c("list", "data.frame"), split = FALSE)
```

Arguments

- text Character vector to be tokenized.
- format Output format. Choose list or data.frame.
- split Logical. If passed as, the function splits the vector into some sentences using `stringi::stri_split_boundaries(type = "sentence")` before tokenizing.

Value

A List or a data.frame.

Examples

```
strj_segment(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  )
)
strj_segment(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  ),
  format = "data.frame"
)
```

strj_tinyseg	<i>Segment text into phrases</i>
--------------	----------------------------------

Description

An alias of strj_tokenize(engine = "tinyseg").

Usage

```
strj_tinyseg(text, format = c("list", "data.frame"), split = FALSE)
```

Arguments

- text Character vector to be tokenized.
- format Output format. Choose list or data.frame.
- split Logical. If passed as TRUE, the function splits vectors into some sentences using stringi::stri_split_boundaries(type = "sentence") before tokenizing.

Value

A list or a data.frame.

Examples

```
strj_tinyseg(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  )
)
```

```

strj_tinyseg(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  ),
  format = "data.frame"
)

```

strj_tokenize

Split text into tokens

Description

Splits text into several tokens using specified tokenizer.

Usage

```

strj_tokenize(
  text,
  format = c("list", "data.frame"),
  engine = c("stringi", "budoux", "tinyseg", "mecab", "sudachipy"),
  rcpath = NULL,
  mode = c("C", "B", "A"),
  split = FALSE
)

```

Arguments

text	Character vector to be tokenized.
format	Output format. Choose list or data.frame.
engine	Tokenizer name. Choose one of 'stringi', 'budoux', 'tinyseg', 'mecab', or 'sudachipy'. Note that the specified tokenizer is installed and available when you use 'mecab' or 'sudachipy'.
rcpath	Path to a setting file for 'MeCab' or 'sudachipy' if any.
mode	Splitting mode for 'sudachipy'.
split	Logical. If passed as TRUE, the function splits the vector into some sentences using stringi::stri_split_boundaries(type = "sentence") before tokenizing.

Value

A list or a data.frame.

Examples

```

strj_tokenize(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  )
)
strj_tokenize(
  paste0(
    "\u3042\u306e\u30a4\u30fc\u30cf\u30c8",
    "\u30fc\u30f4\u30a9\u306e\u3059\u304d",
    "\u3068\u304a\u3063\u305f\u98a8"
  ),
  format = "data.frame"
)

```

strj_transcribe_num	<i>Transcribe Arabic to Kansuji</i>
---------------------	-------------------------------------

Description

Transcribes Arabic integers to Kansuji with auxiliary numerals.

Usage

```
strj_transcribe_num(int)
```

Arguments

int Integers.

Details

As its implementation is limited, this function can only transcribe numbers up to trillions. In case you convert much bigger numbers, try to use the 'arabic2kansuji' package.

Value

A character vector.

Examples

```
strj_transcribe_num(c(10L, 31415L))
```

Index

* datasets

hiroba, [6](#)
polano, [10](#)

bind_lr, [2](#)
bind_tf_idf2, [3](#)

collapse_tokens, [5](#)

get_dict_features, [5](#)

hiroba, [6](#)

lex_density, [7](#)

mute_tokens, [8](#)

ngram_tokenizer, [8](#)

pack, [9](#)
polano, [10](#)
prettify, [10](#)

read_rewrite_def, [11](#)

strj_fill_iter_mark, [12](#)
strj_hiraganize, [12](#)
strj_katakanize, [13](#)
strj_normalize, [14](#)
strj_rewrite_as_def, [14](#)
strj_romanize, [15](#)
strj_segment, [16](#)
strj_tinyseg, [17](#)
strj_tokenize, [18](#)
strj_transcribe_num, [19](#)